

Wall mounted unit

AC fan motor unit for wall mounting

- › High aesthetic cabinet design
- › Optimum air distribution
- › Easy to install
- › Wireless remote control up to 9 m distance
- › 3-speed fan motor
- › Wide operating range
- › Low operating sound level thanks to tangential fan
- › Insulated with self-extinguishing class 1 heat insulation
- › Removable washable air filter (self-extinguishing class 1)



Indoor unit			FWT-GT	02	03	04	05	06
				2-pipe				
Cooling capacity (standard conditions)	Total capacity	High	kW	2.40	2.67	3.27	4.49	5.21
		Medium	kW	2.20	2.23	2.79	4.02	4.32
		Low	kW	1.94	2.02	2.52	3.76	4.04
	Sensible capacity	High	kW	1.82	1.99	2.60	3.38	4.03
		Medium	kW	1.73	1.69	2.21	3.00	3.52
		Low	kW	1.50	1.49	1.91	2.77	3.22
Heating capacity (standard conditions)	High	kW	2.71	2.96	3.71	5.07	6.23	
	Medium	kW	2.41	2.62	3.29	4.51	5.38	
	Low	kW	2.06	2.25	2.75	4.03	4.83	
Power input	High	kW	0.031	0.032	0.042	0.053	0.072	
	Medium	kW	0.03		0.04	0.05	0.07	
	Low	kW	0.03			0.04	0.06	
FCEER				D			C	D
FCCOP				C				
Dimensions	Unit	HeightxWidthxDepth	mm	288x800x206			310x1,070x224	
Weight	Unit		kg	9.00			14.0	
Casing	Colour			White				
Air filter	Type			Washable Saranet				
Fan	Type			Cross flow fan				
	Quantity			1				
	Air flow rate	High	m ³ /h	442	476	629	866	1,053
		Medium	m ³ /h	391	425	544	765	883
Low		m ³ /h	340	374	442	663	782	
Total sound power level	High	dBA	45.0	48.0	55.0		59.0	
	Medium	dBA	41.0	44.0	50.0	51.0	54.0	
	Low	dBA	36.0	39.0	45.0	47.0	51.0	
Sound pressure level	High	dBA	34.0	35.0	42.0		46.0	
	Medium	dBA	29.0	30.0	39.0	38.0	42.0	
	Low	dBA	25.0		32.0	34.0	39.0	
Piping connections	Drain OD	mm	19					
Power supply	Phase/Frequency/Voltage	Hz/V	1N~/50/220-240					
Control systems	Infrared remote control		WRC-HPC					
	Wired remote control		MERCA / SRC-HPA					

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue